

SAMPLE PART NUMBER	F2	22	13	02	2	4	55	0A	LCD	45M
F222 13 0224 550A LCD 45M										
F200 F BEAM™ Mini 2 Cable Assemblies										
Shell Type for first end										
10: Plug										
21: Jam Nut Receptacle - Low Profile										
22: Jam Nut Receptacle - Strain Relief										
23: SQ Flange Receptacle - Low Profile										
24: SQ Flange Receptacle - Strain Relief										
Shell Size										
11										
13										
Number of Channels										
02: 2 Channels										
04: 4 Channels										
Fibre Type										
2: Singlemode 9/125										
4: Multimode 50/125										
Shell Material										
1: Stainless Steel										
4: Aluminium with black zinc nickel										
Cable Diameter										
09: 900µm Buffered Fibre (Low Profile Only)										
30: Standard Zip-Cord - 3.0mm										
55: Tactical Cable - 5.5mm										
Shell Colour										
0A: Black										
9A: Base Material (Stainless Steel Only)										
Connectors for other end										
P: Plug										
JRLP: Jam Nut Receptacle - Low Profile										
JRSR: Jam Nut Receptacle - Strain Relief										
SQLP: SQ Flange Receptacle - Low Profile										
SQSR: SQ Flange Receptacle - Strain Relief										
LCA/FCA/SCA: Telecom connector with angled physical contact 8° for SM only										
LC/LCD (duplex)/SC: Telecom connector available with MM & SM										
For custom requirements please consult us										
Cable Length										
xxxM: customer to specify length in metres, for example 45m										