

SAMPLE PART NUMBER	F6	22	02	2	3	30	1A
<i>F622 0223 550A</i>							
<b>F600 Series FxBEAM™ Junior Connector</b>							
<b>Shell Type</b>							
10: Plug							
21: Jam Nut Receptacle - Low Profile							
<b>22:</b> Jam Nut Receptacle - Strain Relief							
23: SQ Flange Receptacle - Low Profile							
23: SQ Flange Receptacle - Strain Relief							
<b>Number of Channels</b>							
01: 1 Channel							
<b>02:</b> 2 Channels							
04: 4 Channels							
<b>Fibre Type</b>							
<b>2:</b> Singlemode							
4: Multimode							
<b>Shell Material</b>							
1: Stainless Steel							
2: Aluminium Hard Anodised - Non-Conductive (Standard Receptacle)							
<b>3:</b> Aluminium Hard Anodised - Conductive (Standard Plug)							
<b>Cable Diameter</b>							
09: 900µm Buffered Fibre (Low Profile Only)							
<b>30:</b> Standard Zip-Cord - 3.0mm							
55: Tactical Cable - 5.5mm							
<b>Shell Colour</b>							
0A: Black							
<b>1A:</b> Olive Green							
9A: Base Material (Stainless Steel Only)							