SAMPLE PART NUMBER *F723 13 0224 550A LCD 45M*	F7	22	13	02	2	4	55	0A	LCD	45M
F700 D38999 Series III Expanded Beam Assemblies										
Shell Type for first end 10: Plug 21: Jam Nut Receptacle - Low Profile **22**: Jam Nut Receptacle - Strain Relief 23: SQ Flange Receptacle - Low Profile 24: SQ Flange Receptacle - Strain Relief										
Shell Size 11 **13**										
Number of Channels **02**: 2 Channels 04: 4 Channels										
Fibre Type **2**: Singlemode 9/125 4: Multimode 50/125										
Shell Material 1: Stainless Steel 4: Aluminium with black zinc nickel										
Cable Diameter 09: 900µm Buffered Fibre (Low Profile Only) 30: Standard Zip-Cord - 3.0mm **55**: Tactical Cable - 5.5mm										
Shell Colour **0A**: Black 9A: Base Material (Stainless Steel Only)										
Connectors for other end P: Plug JRLP: Jam Nut Receptacle - Low Profile JRSR: Jam Nut Receptacle - Strain Relief SQLP: SQ Flange Receptacle - Low Profile SQSR: SQ Flange Receptacle - Strain Relief LCA/FCA/SCA: Telecom connector with angled physical contact 8° for SM only LC/**LCD** (duplex)/SC: Telecom connector available with MM & SM ***For custom requirements please consult us***										
Cable Length **xxxM:** customer to specifiy length in metres**, for example 45m**										